



ADTTE

TOUCH TRACKER® MATRIX KEYBOARD



FEATURES

- Attractive ergonomic design
- Backlit LCD display
- Camera, monitor and satellite site selection
- Variable-speed Tracker Ball control of pan/tilt and dome
- Lens control (zoom, focus, iris)
- Supports dome "flip" feature
- Preset, pattern and auxiliary control
- Tour control
- Salvo control
- Alarm control
- Supports multiple languages (English, French, Spanish, German, Italian, Portuguese)
- Built-in self-test to verify hardware and software operation

The ADTTE Matrix Switcher/Controller Keyboard is compact, ergonomically-designed and compatible with MegaPower™ Series Matrix Switcher/Controller Systems. This keyboard provides you with easy access to a complete selection of video switching options – from basic camera and monitor selection to the most advanced automatic control.

The tracker ball provides control of fixed and variable-speed pan/tilts and domes. Buttons enable you to control lens zoom, focus, and iris functions. The keypad contains buttons that allow you to assign any camera to any monitor, and access special features such as salvos, tours, and alarms.

The LCD displays the currently selected camera, monitor, and site. It also enables you to see the numbers you enter from the keypad as you enter them, and it displays system prompts and messages.

SPECIFICATIONS

ADTTEMatrix Keyboard, 120 or 230 VAC

[illegible]

Input Voltage 16 to 32 VAC, 50/60 Hz
Power 10.8 watts

Dimensions (H x W x D) 130 x 194 x 260 mm
(5.12 x 7.63 x 10.24 in)
Weight 1 kg (2.2 lbs)
Color Black shell with gray appliqué

Operating Temperature 0° to 50° C (32° to 122° F)
Humidity 5-95% RH (non-condensing)
Storage Temperature -20° to 65° C (-4° to 149° F)

Emissions	FCC: 47 CFR Part 15, Subpart B, Class A CE: EN55022 Class B CE: EN6100-3-2 CE: EN6100-3-3 AS/NZS 3548, Class A CISPR22 ICES-003
Immunity	CE: EN50130-4
Safety	UL: UL1950 cUL: CSA 22.2 No. 950 IEC950 CE: EN60950

(EIM Module and Transformer are supplied with the ADTTE)